

TAPE ADHESIVE MANUAL

Code Antalis : 401121


 antalis
Just ask Antalis


Product description

Material : Aluminium tape,
Adhesive mass : acrylic
Thickness : 40 μ m, Width : 50 mm, Length : 50 m

Box of 24 rolls

Advantage products :

- High resistance to temperature
- Very flexible and highly conformable
- Tearable by hand
- M1 tire rating
- Continuity of the aluminum appearance of the ventilation ducts

Applications :

- Thermal and aeraulic insulation. Heat deflector. Photoelectric detection.

GENERAL FINISHED PRODUCT SPECIFICATIONS

Material	Aluminium
Nature of the adhesive	Acrylic
Adhesion to steel	4.9 N/cm
Elongation	3% (+/-1%)
Width	50 mm (+/-5%)
Length	50 m (+/-5%)
Aluminium thickness	40 μ (+/-8%)
Total thickness	70 μ (+/- 8%)
Tape weight	630 g (+/- 5%)
Mandrel thickness	76 mm (+/- 5%)
Breaking strength	21 N/cm (+/-5%)
Temperature resistance	-20 to +110 ° C
Fire classification (PV No. CM-15-B025)	M1 (NF P 92 - 501: 1995)
UL classification : flame propagation speed	5
UL classification : Developed smoke	0

LOGISTIC SPECIFICATIONS

Number of reels per pallet	1152 reels
Pallet dimensions	1200 x 800 mm
Pallet height	1900 mm

Updated in 2023

Trouvez-nous sur www.antalis.frContactez-nous : packaging.fr@antalis.com

Tous les renseignements fournis ci-dessus sont donnés à titre indicatif et sont susceptibles d'être modifiés par Antalis.